



## HM Series, Crimp Connection, 3/4 pin, Femle insert



**Typecode** HM040-003/4-FC-1  
**ID** 1 007 04 0000048

### Technical Data

#### Product Properties

Series	HM
Mating with	Single module
Connection mode	Crimp termination
Gender	Femle
Rated voltage	830 V
Rated current	40 / 10A
Rated impulse voltage	8 kV
Mating contact	40A(CSF40/CGF40) / 10A(DSF/DGF)
Number of pins	3 / 4
Core cross-section/Clamping ability	1.5 ~ 6 mm <sup>2</sup> /0.14 ~ 2.5 mm <sup>2</sup> AWG16 ~ AWG10 / AWG26 ~ AWG14
Pollution degree	3
Insulation resistance	≥ 10 <sup>10</sup> Ω
Limiting temperature	-40 °C ~ +125 °C
Standard	EN 60664-1, IEC 61984

#### Insert

Material	PC
Colour	RAL 7032

#### Commercial data

Weight	0.010 kg
Packaging unit	1 pc
Country of origin	CN

### Features

- High quality engineering plastics
- Crimp termination
- ≥ 500 Mating cycles
- Approval: CE
- RoHS-compliant

\*这里所列的是设计数据，有关产品的变更不在此做说明，未尽事宜请联系客服。用户有责任验证功能、符合适用的法律和指令以及在特定应用中的电气安全。